



## FDV SPEC SHEET

Galactic C

Art. no: 9057-4-02-2



# Galactic C



Art. no: 9057-4-02-2

| LIGHT TECHNICAL          |                |
|--------------------------|----------------|
| Lightsource Type:        | LED (built in) |
| Lumen Output:            | 3300           |
| Lumen LED (tc=25):       | 4200           |
| Beam Angle:              | 85°            |
| CCT (Color Temperature): | 2700-3000K     |
| CRI / Ra:                | 90             |
| Color Code:              | 927/930        |
| MacAdam (SDCM):          | 3              |
| Lens (Diffuser):         | Micropris.     |

| MOUNTING / CONNECTION |                                    |
|-----------------------|------------------------------------|
| Connection:           | Terminal                           |
| Cut-out [mm]:         | 220-250                            |
| Mounting:             | Partial-recessed, Surface, Pendant |

| ELECTRICAL DATA                     |           |
|-------------------------------------|-----------|
| Dimming:                            | None      |
| Flickerfree:                        | Yes       |
| Standby power Psb (W) <:            | 0,5       |
| Flicker metric (Pst LM) <:          | 1         |
| Stroboscopic effect metric (SVM) <: | 0,4       |
| System Power [W]:                   | 40        |
| System Voltage [V]:                 | 230V 50Hz |
| Protection Class:                   | 1         |
| Max load pr circuit - B10:          | 10        |
| Max load pr circuit - B16:          | 16        |
| Max load pr circuit - C10:          | 17        |
| Max load pr circuit - C16:          | 27        |
| Leakage current [mA]:               | 0,7       |
| Inrush current Imax [A]:            | 18        |
| Inrush current time [µs]:           | 400       |
| Socket / Cap-Base:                  | N/A       |
| Current Output [mA]:                | 1000mA    |



## FDV SPEC SHEET

Galactic C

Art. no: 9057-4-02-2



*Lighting Solutions*

### PRODUCT

|                             |                 |
|-----------------------------|-----------------|
| Ingress Protection:         | IP40            |
| Impact Protection:          | IK03            |
| Operating Temperature [°C]: | -20 - 40        |
| Lifetime [h]:               | L80B10: 100 000 |
| Color:                      | Black           |
| RAL:                        | RAL9005         |
| Length [mm]:                | 400             |
| Height [mm]:                | 102             |
| Width [mm]:                 | 400             |
| Diameter [mm]:              | 400             |
| Weight [kg]:                | 2,85            |
| Housing Material :          | Aluminium 6063  |
| Diffuser Material:          | Polycarbonate   |
| Material 2:                 | SPCC            |