




Silindir Maxi





C € ☐ IP20 230V 50Hz

A⁺

SPECIFICATIONS Lightsource Type: LED (built in) System Power [W]: 28W CCT (Color Temperature): 3000K CRI / Ra: 90 Lumen Output: 2773lm Lumen LED (tc=25): 3400lm Beam Angle: 20° Lens (Diffuser): Clear Dimming: None System Voltage [V]: 230V 50Hz Connection: Track 3-Circuit Mounting: Track, Ceiting Lifetime [h]: L80B10: 60 000h UGR (<=):		
System Power [W]: 28W CCT (Color Temperature): 3000K CRI / Ra: 90 Lumen Output: 2773lm Lumen LED (tc=25): 3400lm Beam Angle: 20° Lens (Diffuser): Clear Dimming: None System Voltage [V]: 230V 50Hz Connection: Track 3-Circuit Mounting: Track, Ceiling Lifetime [h]: L80B10: 60 000h UGR (<=):	SPECIFICATIONS	
CCT (Color Temperature): 3000K CRI / Ra: 90 Lumen Output: 2773lm Lumen LED (tc=25): 3400lm Beam Angle: 20° Lens (Diffuser): Clear Dimming: None System Voltage [V]: 230V 50Hz Connection: Track 3-Circuit Mounting: Track, Ceiling Lifetime [h]: L80B10: 60 000h UGR (<=):	Lightsource Type:	LED (built in)
CRI / Ra: 90 Lumen Output: 2773lm Lumen LED (tc=25): 3400lm Beam Angle: 20° Lens (Diffuser): Clear Dimming: None System Voltage [V]: 230V 50Hz Connection: Track 3-Circuit Mounting: Track, Ceiling Lifetime [h]: L80B10: 60 000h UGR (<=):	System Power [W]:	28W
Lumen Output: 2773lm Lumen LED (tc=25): 3400lm Beam Angle: 20° Lens (Diffuser): Clear Dimming: None System Voltage [V]: 230V 50Hz Connection: Track 3-Circuit Mounting: Track, Ceiling Lifetime [h]: L80B10: 60 000h UGR (<=):	CCT (Color Temperature):	3000K
Lumen LED (tc=25): 3400lm Beam Angle: 20° Lens (Diffuser): Clear Dimming: None System Voltage [V]: 230V 50Hz Connection: Track 3-Circuit Mounting: Track, Ceiling Lifetime [h]: L80B10: 60 000h UGR (<=):	CRI / Ra:	90
Beam Angle: 20° Lens (Diffuser): Clear Dimming: None System Voltage [V]: 230V 50Hz Connection: Track 3-Circuit Mounting: Track, Ceiling Lifetime [h]: L80B10: 60 000h UGR (<=):	Lumen Output:	2773lm
Lens (Diffuser): Clear Dimming: None System Voltage [V]: 230V 50Hz Connection: Track 3-Circuit Mounting: Track, Ceiling Lifetime [h]: L80B10: 60 000h UGR (<=):	Lumen LED (tc=25):	3400lm
Dimming: None System Voltage [V]: 230V 50Hz Connection: Track 3-Circuit Mounting: Track, Ceiling Lifetime [h]: L80B10: 60 000h UGR (<=): 11 Lumen/W: 99lm/W MacAdam (SDCM): 3 Color: Black Height [mm]: 305mm Width [mm]: 85mm	Beam Angle:	20°
System Voltage [V]: 230V 50Hz Connection: Track 3-Circuit Mounting: Track, Ceiling Lifetime [h]: L80B10: 60 000h UGR (<=):	Lens (Diffuser):	Clear
Connection: Track 3-Circuit Mounting: Track, Ceiling Lifetime [h]: L80B10: 60 000h UGR (<=): 11 Lumen/W: 99lm/W MacAdam (SDCM): 3 Color: Black Height [mm]: 305mm Width [mm]: 85mm	Dimming:	None
Mounting: Track, Ceiling Lifetime [h]: L80B10: 60 000h UGR (<=):	System Voltage [V]:	230V 50Hz
Lifetime [h]: UGR (<=): Lumen/W: 99lm/W MacAdam (SDCM): Color: Black Height [mm]: 305mm Width [mm]: 85mm	Connection:	Track 3-Circuit
UGR (<=):	Mounting:	Track, Ceiling
Lumen/W: 99lm/W MacAdam (SDCM): 3 Color: Black Height [mm]: 305mm Width [mm]: 85mm	Lifetime [h]:	L80B10: 60 000h
MacAdam (SDCM): 3 Color: Black Height [mm]: 305mm Width [mm]: 85mm	UGR (<=):	11
Color: Black Height [mm]: 305mm Width [mm]: 85mm	Lumen/W:	99lm/W
Height [mm]: 305mm Width [mm]: 85mm	MacAdam (SDCM):	3
Width [mm]: 85mm	Color:	Black
	Height [mm]:	305mm
Weight [kg]: 13kg	Width [mm]:	85mm
	Weight [kg]:	1,3kg

Silindir Maxi is the most powerful spotlight in the Silindir-series. With 28W, high light output and CRI it is very suitable for stores and showrooms. The spotlight can ble adjusted in all angles to meet every need. Tiltable 90° and 350° rotatable around its own axis. L305mm - Ø85mm