



FDV SPEC SHEET

Montana M

Art. no: 103031-50-GS-1



Lighting Solutions



Montana M



Art. no: 103031-50-GS-1

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	7500
Lumen LED (tc=25):	8250
Beam Angle:	156°*54°
CCT (Color Temperature):	3000K/4000K
CRI / Ra:	70
Color Code:	730/740
MacAdam (SDCM):	5
Lens (Diffuser):	PMMA

MOUNTING / CONNECTION

Connection:	Cable 8m
Cut-out [mm]:	n/a
Mounting:	Mast



FDV SPEC SHEET

Montana M

Art. no: 103031-50-GS-1



Lighting Solutions

PRODUCT		ELECTRICAL DATA	
Ingress Protection:	IP66	Dimming:	None
Impact Protection:	IK08	Flickerfree:	Yes
Corrosion Class:	C4	Standby power Psb (W) <:	0,5
Wind force (EPA) [m2] at 0°:	0,14	Flicker metric (Pst LM) <:	0,016
Operating Temperature [°C]:	-40 - 50	Stroboscopic effect metric (SVM) <	0,054
Lifetime [h]:	L80B10: 100 000	System Power [W]:	50
Color:	Grey	System Voltage [V]:	230V 50Hz
RAL:	Pantone8403C	Protection Class:	2
Length [mm]:	665	Max load pr circuit - B10:	8
Height [mm]:	125	Max load pr circuit - B16:	13
Width [mm]:	250	Max load pr circuit - C10:	14
Diameter [mm]:	76	Max load pr circuit - C16:	22
Weight [kg]:	6,2	Leakage current [mA]:	0,7
Housing Material :	Aluminium	Inrush current Imax [A]:	98
Diffuser Material:	PMMA	Inrush current time [µs]:	108
Material 2:	Driver	Socket / Cap-Base:	N/A
		Current Output [mA]:	65.9
		Voltage Forward Min [V]:	21,7
		Voltage Forward Max [V]:	22,2
		Emergency light [h]:	No Emergency light
		Emergency light testing:	N/A