



**FDV SPEC SHEET**  
T-Line Louvre  
Art. no: 103130-60-3-ddd



# T-Line Louvre



Art. no: 103130-60-3-ddd

LIGHT TECHNICAL	
Lightsource Type:	LED (built in)
Lumen Output:	10441
Lumen LED (tc=25):	11200
Beam Angle:	60°
CCT (Color Temperature):	3000
CRI / Ra:	90
Color Code:	930
MacAdam (SDCM):	3
Lens (Diffuser):	Lens
UGR (<=):	19

MOUNTING / CONNECTION	
Connection:	18i5 DALI Quick connection
Mounting:	Suspended

ELECTRICAL DATA	
Dimming:	DALI
Dimming Phasecut Type:	Leading edge
Flickerfree:	Yes
System Power [W]:	70-40
Preset Power [W]:	70
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	13
Max load pr circuit - B16:	21
Max load pr circuit - C10:	22
Max load pr circuit - C16:	35
Leakage current [mA]:	0,52
Inrush current I <sub>max</sub> [A]:	17,81
Inrush current time [µs]:	288
Current Output [mA]:	400



## FDV SPEC SHEET

T-Line Louvre

Art. no: 103130-60-3-ddd



*Lighting Solutions*

### PRODUCT

Ingress Protection:	IP40
Impact Protection:	IK03
Operating Temperature [°C]:	-25 - 60
Lifetime [h]:	L80B10: 100 000
Color:	White
RAL:	RAL9016
Length [mm]:	1665
Height [mm]:	44
Width [mm]:	62
Weight [kg]:	2,3
Housing Material :	Aluminium
Diffuser Material:	PMMA