



FDV SPEC SHEET

Cosma


Art. no: 103080-03-3-ddd



Lighting Solutions



Cosma



Art. no: 103080-03-3-ddd

LIGHT TECHNICAL

Lightsource Type:	LED (replaceable)
Lumen Output:	1800
Lumen LED (tc=25):	2000
Beam Angle:	130°
CCT (Color Temperature):	30/35/4000K
CRI / Ra:	80
Color Code:	830/835/840
MacAdam (SDCM):	3
Lens (Diffuser):	Opal
UGR (<=):	24

MOUNTING / CONNECTION

Connection:	QuickConnect
Mounting:	Surface, Wall, Ceiling

ELECTRICAL DATA

Dimming:	DALI2
Flickerfree:	Yes
System Power [W]:	15
Preset Power [W]:	15
System Voltage [V]:	230V 50Hz
Protection Class:	2
Socket / Cap-Base:	N/A
Current Output [mA]:	95



FDV SPEC SHEET

Cosma

Art. no: 103080-03-3-ddd



Lighting Solutions

PRODUCT

Ingress Protection:	IP44
Impact Protection:	IK10
Operating Temperature [°C]:	-20 - 40
Lifetime [h]:	L80B10: 100 000
Color:	White
RAL:	RAL9003
Length [mm]:	300
Height [mm]:	68
Width [mm]:	300
Weight [kg]:	0,775