



FDV SPEC SHEET

Cold 10 Mini


Art. no: 1111-50-2



Lighting Solutions



Cold 10 Mini



Art. no: 1111-50-2

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	1390.4
Lumen LED (tc=25):	2000
Beam Angle:	50°
CCT (Color Temperature):	3000
CRI / Ra:	90
Color Code:	927
Lens (Diffuser):	N/A

MOUNTING / CONNECTION

Connection:	EPN0024
Mounting:	Recessed, Ceiling



FDV SPEC SHEET

Cold 10 Mini

Art. no: 1111-50-2



Lighting Solutions

PRODUCT		ELECTRICAL DATA	
Ingress Protection:	IP20	UGR (<=):	9
Impact Protection:	IK00	Dimming:	Phase-Cut
Lifetime [h]:	L80B10: 100 000	Dimming Output Type:	Amplitude Modulation
Color:	Black	Dimming Phasecut Type:	Leading / Trailing edge
RAL:	RAL9003	Flickerfree:	No
Length [mm]:	196	Standby power Psb (W) <:	0,5
Height [mm]:	50	Flicker metric (Pst LM) <:	1
Width [mm]:	33	Stroboscopic effect metric (SVM) <	0,4
Weight [kg]:	0,54	System Power [W]:	21
Housing Material :	Aluminium	System Voltage [V]:	230V 50Hz
Diffuser Material:	Polycarbonate	Protection Class:	2
		Max load pr circuit - B10:	35
		Max load pr circuit - B16:	56
		Max load pr circuit - C10:	52
		Max load pr circuit - C16:	84
		Leakage current [mA]:	0,7
		Inrush current Imax [A]:	5
		Inrush current time [µs]:	300
		Current Output [mA]:	7
		Voltage Forward Min [V]:	27
		Voltage Forward Max [V]:	32