

PRODUCT SHEET

Driver DALI 900mA Panel max 45W (one4all) 18i5 DALI/EPN0034 Art. no: 0300-04



Driver DALI 900mA Panel max 45W (one4all) 18i5 DALI

Tridonic DALI driver preset at 900mA, max 45W. Primary side 0,3m cable with 18i5 DALI (male). Secondary side EPN0034 (female). Can also be used as switch-dim/ push-dim.





| SPECIFICATIONS | |
|----------------------------------|--|
| System Power [W]: | 45W |
| Dimming: | CLO, Corridor, DALI2, Push, Ready2Mains |
| CC or CV: | CC |
| CC [mA]: | 900 - mA |
| CC (forward voltage driver) [V]: | 25 - 50V |
| Max output voltage [V]: | 60 |
| Output Current Tolerance [%]: | 3% |
| Current Ripple [%]: | 2% |
| Current setting: | DALI-2, I-Select 2 Plug (Tridonic), Ready2Ma |
| Expected Lifetime: | 100000h |
| System Voltage [V]: | 230V 50Hz V |
| Protection Class: | 1 or 2 |
| Dimming output type: | Amplitude Modulation |
| Max load pr circuit - B10: | 14 |
| Max load pr circuit - B16: | 23 |
| Max load pr circuit - C10: | 23 |
| Max load pr circuit - C16: | 38 |
| Leakage current [mA]: | 0,16mA |
| Inrush current Imax [A]: | 23A |
| Inrush current time [µs]: | 200µs |
| Manufacture: | Tridonic |
| Primary Connection: | 18i5 DALI male |
| Secondary Connection: | EPN0034 female |
| Length: | 210mm |
| Height: | 30mm |
| Width: | 43mm |
| Weight: | 0,14kg |