



FDV SPEC SHEET

Stream Y

Art. no: 102452-E-02



Stream Y



Art. no: 102452-E-02

LIGHT TECHNICAL		ELECTRICAL DATA	
Lightsource Type:	LED (built in)	Dimming:	None
Lumen Output:	6600	Flickerfree:	Yes
Lumen LED (tc=25):	7200	Standby power P _{sb} (W) <:	0,5
Beam Angle:	120°	Flicker metric (P _{st} LM) <:	1
CCT (Color Temperature):	4000	Stroboscopic effect metric (SVM) <	0,4
CRI / Ra:	80	System Power [W]:	42
Color Code:	840	System Voltage [V]:	230V 50Hz
MacAdam (SDCM):	3	Protection Class:	1
Lens (Diffuser):	PC Opal	Max load pr circuit - B16:	36
		Inrush current I _{max} [A]:	25
		Inrush current time [μs]:	135
		Socket / Cap-Base:	N/A
		Current Output [mA]:	300
		Emergency light [h]:	3 hours
		Emergency light testing:	Selftest
		Emergency lumen out [lm]:	270



FDV SPEC SHEET

Stream Y

Art. no: 102452-E-02



Lighting Solutions

PRODUCT	
Ingress Protection:	IP65
Impact Protection:	IK08
Operating Temperature [°C]:	-20 - 40
Lifetime [h]:	L80B10: 100 000
Color:	Grey
Length [mm]:	1536
Height [mm]:	80
Width [mm]:	76
Housing Material :	Polycarbonate

MOUNTING / CONNECTION	
Connection:	Terminalx2
Through-wiring (mm ²):	5x2,5
Mounting:	Surface, Suspended