



## FDV SPEC SHEET

Nereus M/S 1850lm 830/840/857 60° 12W WH PIR Ø160-170mm


Art. no: 102620-S-60-3



Lighting Solutions



# Nereus M/S 1850lm 830/840/857 60° 12W WH PIR Ø16



Art. no: 102620-S-60-3

### LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	1660
Lumen LED (tc=25):	1850
Beam Angle:	60°
CCT (Color Temperature):	3/4/5700
Preset CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830/840/857

### MOUNTING / CONNECTION

Connection:	QuickConnect
Cut-out [mm]:	Ø160-170mm
Mounting:	Recessed, Ceiling

### PRODUCT

To be recessed in insulation:	Not applicable
Ingress Protection:	IP44
Operating Temperature [°C]:	-20 - 40
Lifetime [h]:	L80B10: 100 000
Color:	White
RAL:	RAL9016

### ELECTRICAL DATA

UGR (<=):	19
Dimming:	Sensor (PIR)
System Power [W]:	12
System Voltage [V]:	230V 50Hz
Protection Class:	2
Socket / Cap-Base:	N/A