



PRODUCT SHEET

Blume

Art. no: 102780-38-3

NORLUX®

Lighting Solutions

Blume



Blume is a top-of-the-line downlight, specifically designed to meet the lighting needs of various applications, including general rooms, hotels, commercial spaces, offices, shops, and schools. With its impressive IK08 protection and IP65 rating, this lamp is ideal for environments requiring extra durability and reliability. Please note that the driver is sold separately.



SPECIFICATIONS

Lightsource Type:	LED (built in)
System Power [W]:	25W
CCT (Color Temperature):	3000K
CRI / Ra:	80
Lumen Output:	2400lm
Lumen LED (tc=25):	2760lm
Beam Angle:	38
Lens (Diffuser):	Lens
Dimming:	Depending on Driver
Flickerfree:	Yes
System Voltage [V]:	230V 50Hz
Connection:	EPN0024
Mounting:	Recessed, Ceiling
Cut-out [mm]:	200-220mm
Lifetime [h]:	L80B10: 100 000h
Lumen/W:	96lm/W
UGR (<=):	19
MacAdam (SDCM):	3
Color:	White
Length [mm]:	235mm
Height [mm]:	81mm
Width [mm]:	235mm
Diameter [mm]:	235mm
Weight [kg]:	1,27kg
Emergency light [h]:	No Emergency light
Emergency light testing:	N/A