




## FDV SPEC SHEET

Arke Bollard

Art. no: 101150-01-10-500-1



# Arke Bollard



Art. no: 101150-01-10-500-1

### LIGHT TECHNICAL

|                          |                |
|--------------------------|----------------|
| Lightsource Type:        | LED (built in) |
| Lumen Output:            | 865            |
| Lumen LED (tc=25):       | 890            |
| CCT (Color Temperature): | 3000           |
| CRI / Ra:                | 80             |
| Lens (Diffuser):         | Clear          |

### MOUNTING / CONNECTION

|             |              |
|-------------|--------------|
| Connection: | QuickConnect |
| Mounting:   | Bollard      |

### PRODUCT

|                             |                |
|-----------------------------|----------------|
| Ingress Protection:         | IP66           |
| Impact Protection:          | IK10           |
| Operating Temperature [°C]: | -30 - 50       |
| Lifetime [h]:               | L80B50: 78 500 |
| Color:                      | Grey           |
| Height [mm]:                | 500            |
| Width [mm]:                 | 165            |
| Weight [kg]:                | 5,5            |

### ELECTRICAL DATA

|                                      |           |
|--------------------------------------|-----------|
| Dimming:                             | None      |
| System Power [W]:                    | 10        |
| System Voltage [V]:                  | 230V 50Hz |
| Protection Class:                    | 1         |
| Max load pr circuit - B10:           | 12        |
| Max load pr circuit - B16:           | 19        |
| Max load pr circuit - C10:           | 20        |
| Max load pr circuit - C16:           | 32        |
| Leakage current [mA]:                | 0,75      |
| Inrush current I <sub>max</sub> [A]: | 50        |
| Inrush current time [μs]:            | 157       |