




FDV SPEC SHEET

Base 5700lm 840 Opal 52W 5x1,5mm2 PG IP66 IK08 L=1541mm DALI

Art. no: 10176083



Base 5700lm 840 Opal 52W 5x1,5mm2 PG IP66 IK08 L=



Art. no: 10176083

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	5700
CCT (Color Temperature):	4000
CRI / Ra:	80
Color Code:	840
Lens (Diffuser):	PC Opal

PRODUCT

Ingress Protection:	IP66
Impact Protection:	IK08
Operating Temperature [°C]:	-25 - 35
Color:	Grey
Length [mm]:	1541
Height [mm]:	67
Width [mm]:	76
Weight [kg]:	2

ELECTRICAL DATA

Dimming:	DALI
System Power [W]:	52
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	12
Max load pr circuit - B16:	19
Max load pr circuit - C10:	20
Max load pr circuit - C16:	31
Inrush current I _{max} [A]:	38
Inrush current time [μs]:	163

MOUNTING / CONNECTION

Connection:	QuickConnect
Through-wiring (mm2):	5x1,5
Mounting:	Ceiling