## **Torres Mini** 17030-6-30-3

NORLUX

Lighting Solutions





This is by far our most popular mini" downlight and it offers huge flexibility, tiltable up to 25 degrees. This downlight has a recessed light source giving a minimum of stray light. The Torres Mini can be supplied with a variety of connector solutions



Lightsource Type:	LED (built in)
System Power [W]:	23W
CCT (Color Temperature):	3000K
CRI / Ra:	80
Lumen Output:	3132lm
Lumen LED (tc=25):	3450lm
Beam Angle:	30°
Lens (Diffuser):	Clear
Dimming:	None
System Voltage [V]:	230V 50Hz
Connection:	18i3 Quick connection
Mounting:	Ceiling, Recessed
Cut-out [mm]:	125mm
Lumen/W:	136lm/W
UGR (<=):	16
MacAdam (SDCM):	3
Color:	White
Length [mm]:	138mm
Height [mm]:	86mm
Width [mm]:	94mm
To be recessed in insulation:	No

125mm





All specifications are nominal values, deviations may occur.

Product specifications are subject to change without notice. Electrical equipment designed to be part of a fixed electrical installation can only be installed by a registered installation company

Norlux AS Borgeskogen 32 3160 Stokke, Norway A\*\* - 🧹