

Trimo

18045-6-20-3





Tired of downlights giving obtrusive annoying stray light? Our Trimo range of downlights guarantees a minimum of stray light, this is accomplished by using a recessed LED light source. The Trimo range has a 18i3 connector and can be supplied with a variety of connector solutions.



| 50Hz | AAA |
|-------------------------------|-----------------------|
| Lightsource Type: | LED (built in) |
| System Power [W]: | 31W |
| CCT (Color Temperature): | 3000K |
| CRI / Ra: | 80 |
| Lumen Output: | 3774lm |
| Lumen LED (tc=25): | 4450lm |
| Beam Angle: | 20° |
| Lens (Diffuser): | Clear |
| Dimming: | None |
| System Voltage [V]: | 230V 50Hz |
| Connection: | 18i3 Quick connection |
| Mounting: | Ceiling, Recessed |
| Cut-out [mm]: | 155mm |
| Lumen/W: | 122lm/W |
| UGR (<=): | 15 |
| MacAdam (SDCM): | 3 |
| Color: | White |
| Length [mm]: | 170mm |
| Height [mm]: | 170mm |
| Width [mm]: | 170mm |
| Weight [kg]: | 1,4kg |
| To be recessed in insulation: | No |
| | |







All specifications are nominal values, deviations may occur.

Product specifications are subject to change without notice.
Electrical equipment designed to be part of a fixed electrical installation can only be installed by a registered installation company