


NORLUX



€⊕	IP20	230V 50Hz	
----	------	--------------	--

SPECIFICATIONS

System Power [W]:30WCCT (Color Temperature):Fresh FoodCRI / Ra:80Lumen Output:2316lmLumen LED (tc=25):2600lmBeam Angle:40°Lens (Diffuser):ClearDimming:NoneSystem Voltage [V]:230V 50HzConnection:Track 3-CircuitMounting:L80B10: 50.000hLifetime [h]:L80B10: 50.000hLumen/W:7/lm/WMacAdam (SDCM):3Color:BlackLength [mm]:180mmWidth [mm]:97mmWidth [mm]:1,1kg	Lightsource Type:	LED (built in)
CRI / Ra:80Lumen Output:2316lmLumen LED (tc=25):2600lmBeam Angle:40°Lens (Diffuser):ClearDimming:NoneSystem Voltage [V]:230V 50HzConnection:Track 3-CircuitMounting:Ceiling, TrackLifetime [h]:L80B10: 50.000hLumen/W:7/lm/WMacAdam (SDCM):3Color:BlackLength [mm]:180mmWidth [mm]:97mm	System Power [W]:	30W
Lumen Output:2316lmLumen LED (tc=25):2600lmBeam Angle:40°Lens (Diffuser):ClearDimming:NoneSystem Voltage [V]:230V 50HzConnection:Track 3-CircuitMounting:Ceiling, TrackLifetime [h]:L80B10: 50.000hLumen/W:7/lm/WMacAdam (SDCM):3Color:BlackLength [mm]:28mmHeight [mm]:180mmWidth [mm]:97mm	CCT (Color Temperature):	Fresh Food
Lumen LED (tc=25):2600ImBeam Angle:40°Lens (Diffuser):ClearDimming:NoneSystem Voltage [V]:230V 50HzConnection:Track 3-CircuitMounting:Ceiling, TrackLifetime [h]:L80B10: 50.000hLumen/W:77lm/WMacAdam (SDCM):3Color:BlackLength [mm]:180mmWidth [mm]:97mm	CRI / Ra:	80
Beam Angle:40°Lens (Diffuser):ClearDimming:NoneSystem Voltage [V]:230V 50HzConnection:Track 3-CircuitMounting:Ceiling, TrackLifetime [h]:L80B10: 50.000hLumen/W:77lm/WMacAdam (SDCM):3Color:BlackLength [mm]:28mmHeight [mm]:180mmWidth [mm]:97mm	Lumen Output:	2316lm
Lens (Diffuser):ClearDimming:NoneSystem Voltage [V]:230V 50HzConnection:Track 3-CircuitMounting:Ceiling, TrackLifetime [h]:L80B10: 50.000hLumen/W:77lm/WMacAdam (SDCM):3Color:BlackLength [mm]:228mmHeight [mm]:180mmWidth [mm]:97mm	Lumen LED (tc=25):	2600lm
Dimming:NoneSystem Voltage [V]:230V 50HzConnection:Track 3-CircuitMounting:Ceiling, TrackLifetime [h]:L80B10: 50.000hLumen/W:77lm/WMacAdam (SDCM):3Color:BlackLength [mm]:228mmHeight [mm]:180mmWidth [mm]:97mm	Beam Angle:	40°
System Voltage [V]:230V 50HzConnection:Track 3-CircuitMounting:Ceiling, TrackLifetime [h]:L80B10: 50.000hLumen/W:77lm/WMacAdam (SDCM):3Color:BlackLength [mm]:228mmHeight [mm]:180mmWidth [mm]:97mm	Lens (Diffuser):	Clear
Connection:Track 3-CircuitMounting:Ceiling, TrackLifetime [h]:L80B10: 50.000hLumen/W:77lm/WMacAdam (SDCM):3Color:BlackLength [mm]:228mmHeight [mm]:180mmWidth [mm]:97mm	Dimming:	None
Mounting:Ceiling, TrackLifetime [h]:L80B10: 50.000hLumen/W:77lm/WMacAdam (SDCM):3Color:BlackLength [mm]:228mmHeight [mm]:180mmWidth [mm]:97mm	System Voltage [V]:	230V 50Hz
Lifetime [h]: L80B10: 50.000h Lumen/W: 77lm/W MacAdam (SDCM): 3 Color: Black Length [mm]: 228mm Height [mm]: 180mm Width [mm]: 97mm	Connection:	Track 3-Circuit
Lumen/W:77lm/WMacAdam (SDCM):3Color:BlackLength [mm]:228mmHeight [mm]:180mmWidth [mm]:97mm	Mounting:	Ceiling, Track
MacAdam (SDCM): 3 Color: Black Length [mm]: 228mm Height [mm]: 180mm Width [mm]: 97mm	Lifetime [h]:	L80B10: 50.000h
Color:BlackLength [mm]:228mmHeight [mm]:180mmWidth [mm]:97mm	Lumen/W:	77lm/W
Length [mm]:228mmHeight [mm]:180mmWidth [mm]:97mm	MacAdam (SDCM):	3
Height [mm]: 180mm Width [mm]: 97mm	Color:	Black
Width [mm]: 97mm	Length [mm]:	228mm
	Height [mm]:	180mm
Weight [kg]: 1,1kg	Width [mm]:	97mm
	Weight [kg]:	1,1kg



Lobus is a small and elegant spotlight for use in track lighting systems. This spotlight has very high lumen output per watt and this puts it in the top segment. The Lobus is very flexible, offering numerous adjustment possibilities making it easy to achieve the perfect light design in stores. The Lobus is available with three different reflectors and comes in three different colors.