**NORLUX®**
*Lighting Solutions*

# Ledline

CE | IP40 | 230V 50Hz | IK08

A++ - A

## SPECIFICATIONS

| | |
|---|---|
| System Power [W]: | 40W |
| CCT (Color Temperature): | 3000K |
| CRI / Ra: | 80 |
| Lumen Output: | 3650lm |
| Lumen LED (tc=25): | 4400lm |
| Beam Angle: | 110 |
| Lens (Diffuser): | Opal |
| Dimming: | None |
| System Voltage [V]: | 230V 50Hz |
| Connection: | LEDLine 5-pin |
| Mounting: | Recessed, Surface, Ceiling, Pendant |
| Lifetime [h]: | L70B50: 50 000h |
| Lumen/W: | 92lm/W |
| Color: | Black |
| Length [mm]: | 1200mm |
| Height [mm]: | 84mm |
| Width [mm]: | 56mm |
| Weight [kg]: | 3,24kg |

1200mm

84mm 56mm

C0 / C180   C90 / C270
cd / 1000 lm

Ledline is a modern linear LED system for seamless lighting. It is based on modular chassis details allowing for seamless extensions through both straight connectors, 90 degrees corners and X-crosses. This allows light designers to make tailor fit lighting systems in an easy manner. The chassis details assure easy installation without failures.