




FDV SPEC SHEET

Ledline

Art. no: 805004-02-3



Ledline



Art. no: 805004-02-3

LIGHT TECHNICAL

Lumen Output:	5950
Lumen LED (tc=25):	7100
Beam Angle:	110
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
Lens (Diffuser):	Opal

MOUNTING / CONNECTION

Connection:	LEDLine 5-pin
Mounting:	Pendant, Ceiling, Surface, Recessed

ELECTRICAL DATA

Dimming:	None
System Power [W]:	75
System Voltage [V]:	230V 50Hz
Protection Class:	2
Max load pr circuit - B10:	5
Max load pr circuit - B16:	8
Max load pr circuit - C10:	8
Max load pr circuit - C16:	14
Leakage current [mA]:	10
Inrush current I _{max} [A]:	120
Inrush current time [μs]:	350
Socket / Cap-Base:	N/A
Voltage Forward Min [V]:	32
Voltage Forward Max [V]:	48



FDV SPEC SHEET

Ledline

Art. no: 805004-02-3



PRODUCT

Ingress Protection:	IP40
Impact Protection:	IK08
Operating Temperature [°C]:	-
Color:	White
Length [mm]:	2400
Height [mm]:	84
Width [mm]:	56
Weight [kg]:	6,6