





FDV SPEC SHEET

Ledline

Art. no: 805014-03-1



Ledline



Art. no: 805014-03-1

LIGHT TECHNICAL

Lumen Output:	9000
Lumen LED (tc=25):	9200
Beam Angle:	110
CCT (Color Temperature):	4000
CRI / Ra:	80
Color Code:	840
Lens (Diffuser):	Opal

MOUNTING / CONNECTION

Connection:	LEDLine 5-pin
Mounting:	Pendant, Ceiling, Surface, Recessed

ELECTRICAL DATA

Dimming:	None
System Power [W]:	75
System Voltage [V]:	230V 50Hz
Protection Class:	2
Max load pr circuit - B10:	18
Max load pr circuit - B16:	28
Max load pr circuit - C10:	18
Max load pr circuit - C16:	28
Leakage current [mA]:	0,7
Inrush current I _{max} [A]:	19
Inrush current time [μs]:	142
Socket / Cap-Base:	N/A



FDV SPEC SHEET

Ledline

Art. no: 805014-03-1



PRODUCT

Ingress Protection:	IP40
Impact Protection:	IK08
Operating Temperature [°C]:	-
Color:	Grey
Length [mm]:	2400
Height [mm]:	84
Width [mm]:	56
Weight [kg]:	6,6