





## FDV SPEC SHEET

Ledline

Art. no: 805020-1



## Ledline



Art. no: 805020-1

### LIGHT TECHNICAL

|                          |      |
|--------------------------|------|
| Lumen Output:            | 3950 |
| Lumen LED (tc=25):       | 3950 |
| Beam Angle:              | 110  |
| CCT (Color Temperature): | 3000 |
| CRI / Ra:                | 90   |
| Color Code:              | 930  |
| Lens (Diffuser):         | Opal |

### MOUNTING / CONNECTION

|             |                                     |
|-------------|-------------------------------------|
| Connection: | LEDLine 5-pin                       |
| Mounting:   | Pendant, Ceiling, Surface, Recessed |

### ELECTRICAL DATA

|                                      |           |
|--------------------------------------|-----------|
| Dimming:                             | DALI      |
| System Power [W]:                    | 50        |
| System Voltage [V]:                  | 230V 50Hz |
| Protection Class:                    | 2         |
| Max load pr circuit - B10:           | 11        |
| Max load pr circuit - B16:           | 18        |
| Max load pr circuit - C10:           | 13        |
| Max load pr circuit - C16:           | 21        |
| Leakage current [mA]:                | 0,25      |
| Inrush current I <sub>max</sub> [A]: | 60        |
| Inrush current time [μs]:            | 3,5       |
| Socket / Cap-Base:                   | N/A       |



## FDV SPEC SHEET

Ledline

Art. no: 805020-1



### PRODUCT

|                             |      |
|-----------------------------|------|
| Ingress Protection:         | IP40 |
| Impact Protection:          | IK08 |
| Operating Temperature [°C]: | -    |
| Color:                      | Grey |
| Length [mm]:                | 1500 |
| Height [mm]:                | 84   |
| Width [mm]:                 | 56   |
| Weight [kg]:                | 4,1  |