



PRODUCT SHEET

Driver 700mA cc 30W (21-43V) Phasecut AcTec JB&EPN0034

Art. no: D70030NT-02



Lighting Solutions

Driver 700mA cc 30W (21-43V) Phasecut AcTec JB&EPN



SPECIFICATIONS

System Power [W]:	30W
Dimming:	Phase-Cut
CC or CV:	CC
CC [mA]:	700 - mA
CC (forward voltage driver) [V]:	21 - 43V
Max output voltage [V]:	43
Output Current Tolerance [%]:	5%
Current Ripple [%]:	50%
Current setting:	None
Expected Lifetime:	30000h
System Voltage [V]:	230V 50Hz V
Protection Class:	2
Dimming Minimum Level :	1%
Dimming Phasecut Type:	Leading / Trailing edge
Max load pr circuit - B10:	140
Max load pr circuit - B16:	224
Max load pr circuit - C10:	280
Max load pr circuit - C16:	448
Leakage current [mA]:	0,5mA
Inrush current I _{max} [A]:	5A
Inrush current time [μs]:	100μs
Manufacture:	AcTEC
Manufacture P/N:	D70030NT - Driver 700mA 30W (21-43V) Pha
Primary Connection:	QuickConnect (L+N)
Secondary Connection:	EPN0034 female
Color:	White
Length:	142mm



PRODUCT SHEET

Driver 700mA cc 30W (21-43V) Phasecut AcTec JB&EPN0034
Art. no: D70030NT-02



Lighting Solutions

Height:	24mm
Width:	50mm
Weight:	0,19kg
Operating Temperature [°C]:	-20 - 50