



FDV SPEC SHEET

Panel


Art. no: 0385-02-3



Lighting Solutions



Panel



Art. no: 0385-02-3

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	3735
Lumen LED (tc=25):	5400
Beam Angle:	110°
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
Lens (Diffuser):	Micropris.
UGR (<=):	19

MOUNTING / CONNECTION

Connection:	EPN0024
Mounting:	Ceiling, Recessed

ELECTRICAL DATA

Dimming:	Depending on Driver
System Power [W]:	33
System Voltage [V]:	230V 50Hz
Protection Class:	2
Max load pr circuit - B10:	14
Max load pr circuit - B16:	24
Max load pr circuit - C10:	24
Max load pr circuit - C16:	40
Inrush current I _{max} [A]:	25
Inrush current time [μs]:	150



FDV SPEC SHEET

Panel

Art. no: 0385-02-3



Lighting Solutions

PRODUCT

Ingress Protection:	IP40
Impact Protection:	IK05
Operating Temperature [°C]:	-
Color:	White
Length [mm]:	595
Height [mm]:	13
Width [mm]:	595