




FDV SPEC SHEET

Tube

Art. no: 30853-6-30-3



Tube



Art. no: 30853-6-30-3

LIGHT TECHNICAL

| | |
|--------------------------|----------------|
| Lightsource Type: | LED (built in) |
| Lumen Output: | 3617 |
| Lumen LED (tc=25): | 4450 |
| Beam Angle: | 30 |
| CCT (Color Temperature): | 3000 |
| CRI / Ra: | 80 |
| Color Code: | 830 |
| MacAdam (SDCM): | 3 |
| Lens (Diffuser): | Clear |

MOUNTING / CONNECTION

| | |
|-------------|-----------------|
| Connection: | Track 3-Circuit |
|-------------|-----------------|

PRODUCT

| | |
|-----------------------------|----------------|
| Ingress Protection: | IP20 |
| Operating Temperature [°C]: | - |
| Lifetime [h]: | L80B50: 50.000 |
| Color: | White |
| Height [mm]: | 197 |
| Width [mm]: | 94 |

ELECTRICAL DATA

| | |
|--------------------------------------|-----------|
| System Power [W]: | 31 |
| System Voltage [V]: | 230V 50Hz |
| Protection Class: | 1 |
| Max load pr circuit - B10: | 14 |
| Max load pr circuit - B16: | 24 |
| Max load pr circuit - C10: | 24 |
| Max load pr circuit - C16: | 40 |
| Inrush current I _{max} [A]: | 25 |
| Inrush current time [μs]: | 150 |
| Socket / Cap-Base: | N/A |
| Current Output [mA]: | 800 |
| Voltage Forward Min [V]: | 29,2 |
| Voltage Forward Max [V]: | 41,6 |