Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Norlux

Supplier's address: Christoffer Martin, Borgeskogen 32, 3160 Stokke, NO

Model identifier: 102320-20-3

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type	NA		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	Yes		
Anti-glare shield:	No	Dimmable:	No

Product parameters					
Parameter		Value	Parameter	Value	
General product parameters:					
•.	nption in on- 00 h), rounded st integer	27	Energy efficiency class	D	
dicating if it refe a sphere (360 ^o)	s flux (фuse), in- ers to the flux in , in a wide cone nrow cone (90º)	3 600 in Nar- row cone (90°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	3 000	
On-mode pow pressed in W	ver (P _{on}), ex-	25,2	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,50	
(P _{net}) for CLS, e	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	90	
Outer dimen-	Height	115	Spectral power dis-	See image	
sions without	Width	97	tribution in the	in last page	
separate con- trol gear, light- ing control	Depth	115	range 250 nm to 800 nm, at full-load	Page 1 /	

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	lf yes, equivalent power (W)	-			
		Chromaticity coordi-	0,420			
		nates (x and y)	0,396			
Parameters for directional light sources:						
Peak luminous intensity (cd)	19 770	Beam angle in de- grees, or the range of beam angles that can be set	20			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	94	Survival factor	1,00			
the lumen maintenance factor	0,97					
(a).	1	, <u> </u>				

(a)'-' : not applicable;

(b)'-' : not applicable;

