





FDV SPEC SHEET

Stream C

Art. no: 0452-02



Lighting Solutions



Stream C



Art. no: 0452-02

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	2580
Lumen LED (tc=25):	2990
Beam Angle:	120
CCT (Color Temperature):	4000
CRI / Ra:	80
Color Code:	840
Lens (Diffuser):	Opal

PRODUCT

Ingress Protection:	IP65
Impact Protection:	IK08
Operating Temperature [°C]:	-20 - 40
Lifetime [h]:	L80B10: 100 000
Color:	Grey
Length [mm]:	602
Height [mm]:	81
Width [mm]:	96

ELECTRICAL DATA

Dimming:	None
System Power [W]:	21
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	65
Max load pr circuit - B16:	110
Max load pr circuit - C10:	75
Max load pr circuit - C16:	120
Leakage current [mA]:	0,45
Inrush current I _{max} [A]:	8
Inrush current time [µs]:	80

MOUNTING / CONNECTION

Connection:	Terminalx2
Through-wiring (mm ²):	5x2,5
Mounting:	Surface, Suspended