



PRODUCT SHEET

Base 5700lm 840 Opal 52W 5x1,5mm2 PG IP66 IK08 L=1541mm DALI
Art. no: 10176083



Lighting Solutions

Base 5700lm 840 Opal 52W 5x1,5mm2 PG IP66 IK08 L=

Base is a sealed industrial light fixture for ceiling surface mounting, indoor and outdoor (under roof). Base have 5x1,5mm2 PG through-wiring and DALI control. Opal PC (IK08) diffuser. Ask for Chemical agents list to check material resistance. Flexible position of mounting clips, also ready for wire-mount. Easy connection of cable - no tools needed.



SPECIFICATIONS

Lightsource Type:	LED (built in)
System Power [W]:	52W
CCT (Color Temperature):	4000K
CRI / Ra:	80
Lumen Output:	5700lm
Lens (Diffuser):	PC Opal
Dimming:	DALI
System Voltage [V]:	230V 50Hz
Connection:	QuickConnect
Mounting:	Ceiling
Lifetime [h]:	L80B50: 70 000h
Lumen/W:	110lm/W
Through-wiring (mm2):	5x1,5
Color:	Grey
Length [mm]:	1541mm
Height [mm]:	67mm
Width [mm]:	76mm
Weight [kg]:	2kg