


Z line







610

Z Line is an LED fixture designed with a focus on energy savings and efficient installation. It utilizes the latest LED technology, providing up to 180 lm/W. The fixture features a 2,5mm2 throughwiring and quick connections on both ends, making installation simple and fast without the need to open the fixture. The fixture is made of galvanized steel and is available in two lengths; 1420mm with 42W in 3000K and 4000K, 1700mm with 42W and 72W in 3000K and 4000K. All versions can be ordered with DALI2.

|--|

| SPECIFICATIONS | |
|------------------|--|
| Lightsource Type | |

| Lightsource Type: | LED (built in) |
|--------------------------|------------------|
| System Power [W]: | 74W |
| CCT (Color Temperature): | 4000K |
| CRI / Ra: | 80 |
| Lumen Output: | 13580lm |
| Lumen LED (tc=25): | 14200lm |
| Beam Angle: | 70° |
| Lens (Diffuser): | Lens |
| Dimming: | None |
| Flickerfree: | Yes |
| System Voltage [V]: | 230V 50Hz |
| Connection: | QuickConnect |
| Mounting: | Surface, Ceiling |
| Lifetime [h]: | L80B10: 100 000h |
| Lumen/W: | 184lm/W |
| MacAdam (SDCM): | 3 |
| Through-wiring (mm2): | 5x2,5 |
| Color: | Steel |
| Length [mm]: | 1700mm |
| Height [mm]: | 69mm |
| Width [mm]: | 86mm |
| Weight [kg]: | 4kg |