




FDV SPEC SHEET
 Universal IP44
 Art. no: 8076-105-3-ddd



Universal IP44



Art. no: 8076-105-3-ddd

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	3860
Lumen LED (tc=25):	4200
Beam Angle:	105°
CCT (Color Temperature):	4000
CRI / Ra:	80
Color Code:	840
MacAdam (SDCM):	3
Lens (Diffuser):	PMMA Opal

MOUNTING / CONNECTION

Connection:	QuickConnect
Through-wiring (mm2):	5x2,5
Mounting:	Surface, Ceiling

ELECTRICAL DATA

Dimming:	DALI2
System Power [W]:	31
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	15
Max load pr circuit - B16:	24
Leakage current [mA]:	0,5
Inrush current I _{max} [A]:	20
Inrush current time [μs]:	200
Socket / Cap-Base:	N/A



FDV SPEC SHEET

Universal IP44

Art. no: 8076-105-3-ddd



Lighting Solutions

PRODUCT

Ingress Protection:	IP44
Operating Temperature [°C]:	-20 - 25
Lifetime [h]:	L80B10: 100 000
Color:	White
Length [mm]:	1200
Height [mm]:	50
Width [mm]:	160
Weight [kg]:	2,9