



FDV SPEC SHEET

Bladeline

Art. no: 013977-01-3



Lighting Solutions



Bladeline



Art. no: 013977-01-3

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	4787/9244
Lumen LED (tc=25):	5300/10300
Beam Angle:	110°
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
MacAdam (SDCM):	3
Lens (Diffuser):	Clear

PRODUCT

Ingress Protection:	IP20
Operating Temperature [°C]:	-10 - 40
Color:	White
Length [mm]:	1560
Height [mm]:	109
Width [mm]:	160
Weight [kg]:	1,15

ELECTRICAL DATA

Dimming:	None
System Power [W]:	36/77
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	10
Max load pr circuit - B16:	16
Max load pr circuit - C10:	16
Max load pr circuit - C16:	26
Leakage current [mA]:	0,25
Inrush current I _{max} [A]:	32
Inrush current time [µs]:	251
Socket / Cap-Base:	N/A
Current Output [mA]:	500/1000
Voltage Forward Min [V]:	32,5
Voltage Forward Max [V]:	34,5

MOUNTING / CONNECTION

Connection:	QuickConnect
Mounting:	Ceiling