

PRODUCT SHEET

Driver DALI 900mA Panel max 45W (one4all) 18i5 DALI/EPN0034 Art. no: 0300-04



Driver DALI 900mA Panel max 45W (one4all) 18i5 DALI

Tridonic DALI driver preset at 900mA, max 45W. Primary side 0,3m cable with 18i5 DALI (male). Secondary side EPN0034 (female). Can also be used as switch-dim/ push-dim.





SPECIFICATIONS	
System Power [W]:	45W
Dimming:	CLO, Corridor, DALI2, Push, Ready2Mains
CC or CV:	CC
CC [mA]:	900 - mA
CC (forward voltage driver) [V]:	25 - 50V
Max output voltage [V]:	60
Output Current Tolerance [%]:	3%
Current Ripple [%]:	2%
Current setting:	DALI-2, I-Select 2 Plug (Tridonic), Ready2Ma
Expected Lifetime:	100000h
System Voltage [V]:	230V 50Hz V
Protection Class:	1 or 2
Max load pr circuit - B10:	14
Max load pr circuit - B16:	23
Max load pr circuit - C10:	23
Max load pr circuit - C16:	38
Leakage current [mA]:	0,16mA
Inrush current Imax [A]:	23A
Inrush current time [µs]:	200μs
Manufacture:	Tridonic
Primary Connection:	18i5 DALI male
Secondary Connection:	EPN0034 female
Length:	210mm
Height:	30mm
Width:	43mm
Weight:	0,14kg