



## PRODUCT SHEET

Driver On/Off 400mA max 17.6W 27-44V 18i3 Male/ EPN0034

Art. no: 0300-23



*Lighting Solutions*

# Driver On/Off 400mA max 17.6W 27-44V 18i3 Male/ EP

Tridonic On/Off driver preset at 400mA, max 17,6W.

Primary side 0,3m cable with 18i3 (male).

Secondary side EPN0034 (female).



### SPECIFICATIONS

System Power [W]:	25W
Dimming:	None
CC or CV:	CC
CC [mA]:	400 - mA
CC (forward voltage driver) [V]:	27 - 44V
Max output voltage [V]:	60
Output Current Tolerance [%]:	7,5%
Current Ripple [%]:	5%
Current setting:	ADV Plug (Tridonic)
Expected Lifetime:	100000h
System Voltage [V]:	230V 50Hz V
Protection Class:	1 or 2
Max load pr circuit - B10:	14
Max load pr circuit - B16:	24
Max load pr circuit - C10:	24
Max load pr circuit - C16:	40
Inrush current I <sub>max</sub> [A]:	25A
Inrush current time [μs]:	150μs
Manufacture:	Tridonic
Primary Connection:	18i3 male
Secondary Connection:	EPN0034 female