



Panel









Panel LED is a light fixture for interior use. It is constructed for fitting in to suspended ceilings. Panel LEDs can be installed as a pendant or mounted on ceiling surfaces. The Panel LED has an opal or micro prismatic diffusor. Choose between ON/OFF, Phase-Cut or DALI2 (CLO, Corridor, Push dim and Ready2mains) driver. See accessories for detailed information.

CE	IP40	230V 50Hz	IK05	

SPECIFICATIONS

Lightsource Type:	LED (
System Power [W]:	36W
CCT (Color Temperature):	4000
CRI / Ra:	80
Lumen Output:	43991
Lumen LED (tc=25):	4900
Beam Angle:	110°
Lens (Diffuser):	Opal
Dimming:	Depe
System Voltage [V]:	230V
Connection:	EPN0
Mounting:	Rece
Lifetime [h]:	L80B
Lumen/W:	122lm
Color:	White
Length [mm]:	1195n
Height [mm]:	8,6m
Width [mm]:	295m
Weight [kg]:	2,6kg



	LED (built in)
	36W
re):	4000K
	80
	4399lm
	4900lm
	110°
	Opal
	Depending on Driver
	230V 50Hz
	EPN0024
	Recessed, Ceiling
	L80B10: 100 000h
	122lm/W
	White
	1195mm
	8,6mm
	295mm
	2,6kg