



FDV SPEC SHEET

Talos 1100lm 830 100° 8W Black IP54 w/Sockets Phasecut
Art. no: 102070-100-2-p



Talos 1100lm 830 100° 8W Black IP54 w/Sockets Phas



Art. no: 102070-100-2-p

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	968
Lumen LED (tc=25):	1100
Beam Angle:	100°
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
MacAdam (SDCM):	3
Lens (Diffuser):	Clear

MOUNTING / CONNECTION

Connection:	QuickConnect
Mounting:	Wall

ELECTRICAL DATA

Dimming:	Phase-Cut
Dimming Phasecut Type:	Leading / Trailing edge
Flickerfree:	Yes
System Power [W]:	8
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	111
Max load pr circuit - B16:	178
Max load pr circuit - C10:	111
Max load pr circuit - C16:	178
Socket / Cap-Base:	N/A
Current Output [mA]:	180
Voltage Forward Min [V]:	30
Voltage Forward Max [V]:	40



FDV SPEC SHEET

Talos 1100lm 830 100° 8W Black IP54 w/Sockets Phasecut

Art. no: 102070-100-2-p



Lighting Solutions

PRODUCT

Ingress Protection:	IP54
Impact Protection:	IK06
Operating Temperature [°C]:	-20 - 45
Lifetime [h]:	L80B10: 50.000
Color:	Black
RAL:	RAL9005
Length [mm]:	180
Height [mm]:	85
Width [mm]:	85
Weight [kg]:	0,92
Housing Material :	Aluminium