



FDV SPEC SHEET

Stream I 6800lm 840 Opal 120° 40W 5x2,5 L:1500mm

Art. no: 102431-02



Lighting Solutions



Stream I 6800lm 840 Opal 120° 40W 5x2,5 L:1500mm



Art. no: 102431-02

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	6240
Lumen LED (tc=25):	6800
Beam Angle:	120°
CCT (Color Temperature):	4000
CRI / Ra:	80
Color Code:	840
Lens (Diffuser):	Opal

ELECTRICAL DATA

Dimming:	None
Flicker metric (Pst LM) <:	1
Stroboscopic effect metric (SVM) <:	0,4
System Power [W]:	40
System Voltage [V]:	230V 50Hz
Protection Class:	2
Max load pr circuit - B10:	33
Max load pr circuit - B16:	54
Max load pr circuit - C10:	56
Max load pr circuit - C16:	90
Leakage current [mA]:	0,7
Inrush current I _{max} [A]:	16
Inrush current time [µs]:	170
Socket / Cap-Base:	N/A

MOUNTING / CONNECTION

Connection:	QuickConnect
Through-wiring (mm2):	5x2,5
Mounting:	Surface, Wall, Ceiling, Pendant



FDV SPEC SHEET

Stream I 6800lm 840 Opal 120° 40W 5x2,5 L:1500mm

Art. no: 102431-02



Lighting Solutions

PRODUCT

Ingress Protection:	IP65
Impact Protection:	IK08
Operating Temperature [°C]:	-20 - 35
Lifetime [h]:	L80B10: 100 000
Color:	Grey
Length [mm]:	1500
Height [mm]:	84,5
Width [mm]:	79,5
Weight [kg]:	2
Housing Material :	Polycarbonate