




Stream Y







| SPECIFICATIONS | |
|--------------------------|--------------------|
| Lightsource Type: | LED (built in) |
| System Power [W]: | 18W |
| CCT (Color Temperature): | 4000K |
| CRI / Ra: | 80 |
| Lumen Output: | 2500lm |
| Lumen LED (tc=25): | 2500lm |
| Beam Angle: | 120° |
| Lens (Diffuser): | PC Opal |
| Dimming: | None |
| System Voltage [V]: | 230V 50Hz |
| Connection: | Terminalx2 |
| Mounting: | Surface, Suspended |
| Lifetime [h]: | L80B10: 100 000h |
| Lumen/W: | 139lm/W |
| MacAdam (SDCM): | 3 |
| Through-wiring (mm2): | 5x2,5 |
| Color: | Grey |
| Length [mm]: | 670mm |
| Height [mm]: | 80mm |
| Width [mm]: | 76mm |

Stream Y is a sealed industrial light fixture for ceiling surface mounting or pendant installation. The Stream is classified in accordance with IP65 and 20,5mmw through wire and is suited for use in garage, industry, and warehouse. The light fixture is equipped with a milky white (opal, polycarbonate) diffusor. Can be delivered with microwave sensor for wireless control between luminaires with Norlux Wireless Connect control.