



## PRODUCT SHEET

Stream Y

Art. no: 102452-02



Lighting Solutions

# Stream Y



| SPECIFICATIONS           |                    |
|--------------------------|--------------------|
| Lightsource Type:        | LED (built in)     |
| System Power [W]:        | 42W                |
| CCT (Color Temperature): | 4000K              |
| CRI / Ra:                | 80                 |
| Lumen Output:            | 6600lm             |
| Lumen LED (tc=25):       | 7200lm             |
| Beam Angle:              | 120°               |
| Lens (Diffuser):         | PC Opal            |
| Dimming:                 | None               |
| System Voltage [V]:      | 230V 50Hz          |
| Connection:              | Terminalx2         |
| Mounting:                | Surface, Suspended |
| Lifetime [h]:            | L80B10: 100 000h   |
| Lumen/W:                 | 157lm/W            |
| MacAdam (SDCM):          | 3                  |
| Through-wiring (mm2):    | 5x2,5              |
| Color:                   | Grey               |
| Length [mm]:             | 1536mm             |
| Height [mm]:             | 80mm               |
| Width [mm]:              | 76mm               |

Stream Y is a sealed industrial light fixture for ceiling surface mounting or pendant installation. The Stream is classified in accordance with IP65 and 2,5mm<sup>2</sup> through wire and is suited for use in garage, industry, and warehouse. The light fixture is equipped with a milky white (opal, polycarbonate) diffuser. Can be delivered with microwave sensor for wireless control between luminaires with Norlux Wireless Connect control.