



FDV SPEC SHEET

Universal G2 IP44 Base

Art. no: 102471-105-3



Lighting Solutions



Universal G2 IP44 Base



Art. no: 102471-105-3

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	2950
Lumen LED (tc=25):	3200
Beam Angle:	105°
CCT (Color Temperature):	3000-4000K
CRI / Ra:	80
Color Code:	830/840
MacAdam (SDCM):	3
Lens (Diffuser):	Micropris.
UGR (<=):	24

MOUNTING / CONNECTION

Connection:	Quickconnectx2
Through-wiring (mm2):	5x2,5
Mounting:	Surface, Ceiling

ELECTRICAL DATA

Dimming:	None
Flickerfree:	Yes
System Power [W]:	20/16/13/11
System Voltage [V]:	230V 50Hz
Protection Class:	1



FDV SPEC SHEET

Universal G2 IP44 Base

Art. no: 102471-105-3



Lighting Solutions

PRODUCT

Ingress Protection:	IP44
Impact Protection:	IK07
Operating Temperature [°C]:	-20 - 40
Lifetime [h]:	L80B10: 100 000
Color:	White
RAL:	RAL9016
Length [mm]:	600
Height [mm]:	52
Width [mm]:	155
Weight [kg]:	1,43
Housing Material :	Metal