




FDV SPEC SHEET

C Line Base

Art. no: 102512-00-1



C Line Base



Art. no: 102512-00-1

LIGHT TECHNICAL

Lightsource Type:	LED (replaceable)
Lumen Output:	16500
Lumen LED (tc=25):	18000
Beam Angle:	60°
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
MacAdam (SDCM):	3
Lens (Diffuser):	Clear

PRODUCT

Ingress Protection:	IP23
Impact Protection:	IK08
Lifetime [h]:	L80: 100 000
Color:	Steel
Length [mm]:	1550
Height [mm]:	50
Width [mm]:	76
Weight [kg]:	2,54

ELECTRICAL DATA

Dimming:	None
Flickerfree:	Yes
Flicker metric (Pst LM) <:	0,011
Stroboscopic effect metric (SVM) <:	0,001
System Power [W]:	100/83/65/57/48
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	11
Max load pr circuit - B16:	17
Max load pr circuit - C10:	17
Max load pr circuit - C16:	27
Inrush current I _{max} [A]:	25,46
Inrush current time [µs]:	395
Current Output [mA]:	75

MOUNTING / CONNECTION

Connection:	QuickConnect
Mounting:	Surface, Ceiling