





## **Cold 5 Outdoor**







IP65 version of the popular Cold -series. With its rectangular shape and recessed light source, Cold provides a unique decorative design. Se accessories for recommended driver. Cut-out 130x36mm.

| (                                | C € III IP65 230V 50Hz |  |
|----------------------------------|------------------------|--|
| SPECIFICATIONS Lightsource Type: |                        |  |
|                                  |                        |  |

| 3012                          |                     |  |  |
|-------------------------------|---------------------|--|--|
| SPECIFICATIONS                |                     |  |  |
| Lightsource Type:             | LED (built in)      |  |  |
| System Power [W]:             | 10W                 |  |  |
| CCT (Color Temperature):      | 3000K               |  |  |
| CRI / Ra:                     | 90                  |  |  |
| Lumen Output:                 | 688lm               |  |  |
| Lumen LED (tc=25):            | 1050lm              |  |  |
| Beam Angle:                   | 30°                 |  |  |
| Lens (Diffuser):              | Clear               |  |  |
| Dimming:                      | Depending on Driver |  |  |
| System Voltage [V]:           | 230V 50Hz           |  |  |
| Connection:                   | Depending on driver |  |  |
| Mounting:                     | Recessed, Ceiling   |  |  |
| Cut-out [mm]:                 | 130x37mm            |  |  |
| Lifetime [h]:                 | L80B10: 100 000h    |  |  |
| UGR (<=):                     | 12                  |  |  |
| MacAdam (SDCM):               | 2                   |  |  |
| Color:                        | Black               |  |  |
| Length [mm]:                  | 143mm               |  |  |
| Height [mm]:                  | 58mm                |  |  |
| Width [mm]:                   | 52mm                |  |  |
| Weight [kg]:                  | 0,47kg              |  |  |
| To be recessed in insulation: | No                  |  |  |