




FDV SPEC SHEET


Torres Mini

Art. no: 17030-7-20-2



Lighting Solutions

 125mm



Torres Mini



Art. no: 17030-7-20-2

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	2730
Lumen LED (tc=25):	3650
Beam Angle:	20°
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
Lens (Diffuser):	Clear

MOUNTING / CONNECTION

Connection:	18i3 Quick connection
Cut-out [mm]:	Ø125
Mounting:	Recessed, Ceiling

ELECTRICAL DATA

Dimming:	None
System Power [W]:	22
System Voltage [V]:	230V 50Hz
Protection Class:	2
Max load pr circuit - B10:	55
Max load pr circuit - B16:	90
Max load pr circuit - C10:	65
Max load pr circuit - C16:	100
Inrush current I _{max} [A]:	8
Inrush current time [µs]:	100
Socket / Cap-Base:	N/A
Current Output [mA]:	600



FDV SPEC SHEET

Torres Mini

Art. no: 17030-7-20-2



Lighting Solutions

PRODUCT

To be recessed in insulation:	No
Ingress Protection:	IP20
Color:	Black
Length [mm]:	138
Height [mm]:	86
Width [mm]:	94