


Torres Mini



🕭 125mm



This is by far our most popular mini" downlight and it offers huge flexibility, tiltable up to 25 degrees. This downlight has a recessed light source giving a minimum of stray light. The Torres Mini can be supplied with a variety of connector solutions.





Lightsource Type:LED (built in)System Power [W]:22WCCT (Color Temperature):3000KCRI / Ra:80Lumen Output:2780lmLumen LED (tc=25):3650lmBeam Angle:40°Lens (Diffuser):ClearDimming:3000 SOHZSystem Voltage [V]:230V 50HZConnection:18i3 Quick connectionMounting:Recessed, CeilingCut-out [mm]:138mmLength [mm]:138mmHeight [mm]:94mmWidth [mm]:No	SPECIFICATIONS	
CCT (Color Temperature):3000KCRI / Ra:80Lumen Output:2780lmLumen LED (tc=25):3650lmBeam Angle:40°Lens (Diffuser):ClearDimming:NoneSystem Voltage [V]:230V 50HzConnection:18i3 Quick connectionMounting:Recessed, CeilingCut-out [mm]:Ø125mmColor:WhiteLength [mm]:138mmHeight [mm]:94mm	Lightsource Type:	LED (built in)
CRI / Ra:80Lumen Output:2780lmLumen LED (tc=25):3650lmBeam Angle:40°Lens (Diffuser):ClearDimming:NoneSystem Voltage [V]:230V 50HzConnection:18i3 Quick connectionMounting:Recessed, CeilingCut-out [mm]:0/125mmColor:WhiteLength [mm]:138mmHeight [mm]:86mmWidth [mm]:94mm	System Power [W]:	22W
Lumen Output:2780lmLumen LED (tc=25):3650lmBeam Angle:40°Lens (Diffuser):ClearDimming:NoneSystem Voltage [V]:230V 50HzConnection:18i3 Quick connectionMounting:Recessed, CeilingCut-out [mm]:Ø125mmColor:WhiteLength [mm]:138mmHeight [mm]:86mmWidth [mm]:94mm	CCT (Color Temperature):	3000K
Lumen LED (tc=25):3650lmBeam Angle:40°Lens (Diffuser):ClearDimming:NoneSystem Voltage [V]:230V 50HzConnection:18i3 Quick connectionMounting:Recessed, CeilingCut-out [mm]:Ø125mmColor:WhiteLength [mm]:138mmHeight [mm]:86mmWidth [mm]:94mm	CRI / Ra:	80
Beam Angle:40°Lens (Diffuser):ClearDimming:NoneSystem Voltage [V]:230V 50HzConnection:18i3 Quick connectionMounting:Recessed, CeilingCut-out [mm]:Ø125mmColor:WhiteLength [mm]:138mmHeight [mm]:86mmWidth [mm]:94mm	Lumen Output:	2780lm
Lens (Diffuser):ClearDimming:NoneSystem Voltage [V]:230V 50HzConnection:18i3 Quick connectionMounting:Recessed, CeilingCut-out [mm]:Ø125mmColor:WhiteLength [mm]:138mmHeight [mm]:86mmWidth [mm]:94mm	Lumen LED (tc=25):	3650lm
Dimming:NoneSystem Voltage [V]:230V 50HzConnection:18i3 Quick connectionMounting:Recessed, CeilingCut-out [mm]:Ø125mmColor:WhiteLength [mm]:138mmHeight [mm]:86mmWidth [mm]:94mm	Beam Angle:	40°
System Voltage [V]:230V 50HzConnection:18i3 Quick connectionMounting:Recessed, CeilingCut-out [mm]:Ø125mmColor:WhiteLength [mm]:138mmHeight [mm]:86mmWidth [mm]:94mm	Lens (Diffuser):	Clear
Connection:18i3 Quick connectionMounting:Recessed, CeilingCut-out [mm]:Ø125mmColor:WhiteLength [mm]:138mmHeight [mm]:86mmWidth [mm]:94mm	Dimming:	None
Mounting:Recessed, CeilingCut-out [mm]:Ø125mmColor:WhiteLength [mm]:138mmHeight [mm]:86mmWidth [mm]:94mm	System Voltage [V]:	230V 50Hz
Cut-out [mm]:Ø125mmColor:WhiteLength [mm]:138mmHeight [mm]:86mmWidth [mm]:94mm	Connection:	18i3 Quick connection
Color:WhiteLength [mm]:138mmHeight [mm]:86mmWidth [mm]:94mm	Mounting:	Recessed, Ceiling
Length [mm]:138mmHeight [mm]:86mmWidth [mm]:94mm	Cut-out [mm]:	Ø125mm
Height [mm]:86mmWidth [mm]:94mm	Color:	White
Width [mm]: 94mm	Length [mm]:	138mm
	Height [mm]:	86mm
To be recessed in insulation: No	Width [mm]:	94mm
	To be recessed in insulation:	No

NORLUX AS | Borgeskogen 32, 3160 Stokke | post@norlux.com | +47 33 30 10 80 | www.norlux.com

A** - A