




Acrux Adjustable



1 82-88mm






CE	IP54	230V 50Hz	IK06	

SPECIFICATIONS

System Power [W]:10WCCT (Color Temperature):2700KCRI / Ra:90Lumen Output:650lmLumen LED (tc=25):650lmBeam Angle:36°Lens (Diffuser):ClearDimming:Phase-CutSystem Voltage [V]:230V 50HzConnection:QuickConnectMounting:Recessed, CeilingCut-out [mm]:482-Ø88mmLifetime [h]:L80B10: 50.000hLumen/W:61lm/WMacAdam (SDCM):3Color:WhiteHeight [mm]:55mmWidth [mm]:95mmTo be recessed in insulation:No	Lightsource Type:	LED (built in)	
CRI / Ra:90Lumen Output:650ImLumen LED (tc=25):650ImBeam Angle:36°Lens (Diffuser):ClearDimming:Phase-CutSystem Voltage [V]:230V 50HzConnection:QuickConnectMounting:Recessed, CeilingCut-out [mm]:882-Ø88mmLifetime [h]:L80810: 50.000hLumen/W:61Im/WMacAdam (SDCM):3Color:WhiteHeight [mm]:55mmWidth [mm]:95mm	System Power [W]:	10W	
Lumen Output:650 lmLumen LED (tc=25):650 lmBeam Angle:36°Lens (Diffuser):ClearDimming:Phase-CutSystem Voltage [V]:230V 50HzConnection:QuickConnectMounting:Recessed, CeilingCut-out [mm]:k82-Ø88mmLifetime [h]:L80B10: 50.000hLumen/W:61lm/WMacAdam (SDCM):3Color:WhiteHeight [mm]:55mmWidth [mm]:95mm	CCT (Color Temperature):	2700К	
Lumen LED (tc=25):650 lmBeam Angle:36°Lens (Diffuser):ClearDimming:Phase-CutSystem Voltage [V]:230V 50HzConnection:QuickConnectMounting:Recessed, CeilingCut-out [mm]:Ø82-Ø88mmLifetime [h]:L80B10: 50.000hLumen/W:61lm/WMacAdam (SDCM):3Color:WhiteHeight [mm]:55mmWidth [mm]:95mm	CRI / Ra:	90	
Beam Angle:36°Lens (Diffuser):ClearDimming:Phase-CutSystem Voltage [V]:230V 50HzConnection:QuickConnectMounting:Recessed, CeilingCut-out [mm]:Ø82-Ø88mmLifetime [h]:L80B10: 50.000hLumen/W:61lm/WMacAdam (SDCM):3Color:WhiteHeight [mm]:55mmWidth [mm]:95mm	Lumen Output:	650lm	
Lens (Diffuser):ClearDimming:Phase-CutSystem Voltage [V]:230V 50HzConnection:QuickConnectMounting:Recessed, CeilingCut-out [mm]:Ø82-Ø88mmLifetime [h]:L80B10: 50.000hLumen/W:61lm/WMacAdam (SDCM):3Color:WhiteHeight [mm]:55mmWidth [mm]:95mm	Lumen LED (tc=25):	650lm	
Dimming:Phase-CutSystem Voltage [V]:230V 50HzConnection:QuickConnectMounting:Recessed, CeilingCut-out [mm]:Ø82-Ø88mmLifetime [h]:L80B10: 50.000hLumen/W:61lm/WMacAdam (SDCM):3Color:WhiteHeight [mm]:55mmWidth [mm]:95mm	Beam Angle:	36°	
System Voltage [V]:230V 50HzConnection:QuickConnectMounting:Recessed, CeilingCut-out [mm]:Ø82-Ø88mmLifetime [h]:L80B10: 50.000hLumen/W:61lm/WMacAdam (SDCM):3Color:WhiteHeight [mm]:55mmWidth [mm]:95mm	Lens (Diffuser):	Clear	
Connection:QuickConnectMounting:Recessed, CeilingCut-out [mm]:Ø82-Ø88mmLifetime [h]:L80B10: 50.000hLumen/W:61lm/WMacAdam (SDCM):3Color:WhiteHeight [mm]:55mmWidth [mm]:95mm	Dimming:	Phase-Cut	
Mounting:Recessed, CeilingCut-out [mm]:Ø82-Ø88mmLifetime [h]:L80B10: 50.000hLumen/W:61lm/WMacAdam (SDCM):3Color:WhiteHeight [mm]:55mmWidth [mm]:95mm	System Voltage [V]:	230V 50Hz	
Cut-out [mm]: Ø82-Ø88mm Lifetime [h]: L80B10: 50.000h Lumen/W: 61lm/W MacAdam (SDCM): 3 Color: White Height [mm]: 55mm Width [mm]: 95mm	Connection:	QuickConnect	
Lifetime [h]: L80B10: 50.000h Lumen/W: 61lm/W MacAdam (SDCM): 3 Color: White Height [mm]: 55mm Width [mm]: 95mm	Mounting:	Recessed, Ceiling	
Lumen/W:61lm/WMacAdam (SDCM):3Color:WhiteHeight [mm]:55mmWidth [mm]:95mm	Cut-out [mm]:	Ø82-Ø88mm	
MacAdam (SDCM): 3 Color: White Height [mm]: 55mm Width [mm]: 95mm	Lifetime [h]:	L80B10: 50.000h	
Color:WhiteHeight [mm]:55mmWidth [mm]:95mm	Lumen/W:	61lm/W	
Height [mm]: 55mm Width [mm]: 95mm	MacAdam (SDCM):	3	
Width [mm]: 95mm	Color:	White	
	Height [mm]:	55mm	
To be recessed in insulation: No	Width [mm]:	95mm	
	To be recessed in insulation:	No	



Adjustable downligth with IP54 classification. Low glare and secluded light source and with modern reflector. Suitable for all rooms included bathroom. Complete with dimmable driver and quick connect for easy installation.