

Tigrus Tiltable


To be recessed in insulation:

SPECIFICATIONS System Power [W]:



7W

🕭 76-83mm



	190"	180"	150"	
120° 60° 60°				90°
	\sim	_Y	\sim	
C0 / C180	30°	0*	30° C9	0/0220
		cd / 1000 lm	Ca	/ Sagro

Tigrus Tiltable can be mounted directly in insulation. Tigrus has CRI>95 and is delivered with 2700K or Dim2Warm. The downlight can be tilted 25°. Easy to connect without using a screwdriver. Cut-out 76-83mm.

CCT (Color Temperature):	3000K	
CRI / Ra:	95	
Lumen Output:	530lm	
Lumen LED (tc=25):	550lm	
Beam Angle:	36°	
Lens (Diffuser):	Clear	
Dimming:	Phase-Cut	
Flickerfree:	Yes	
System Voltage [V]:	230V 50Hz	
Connection:	QuickConnect	
Mounting:	Recessed, Ceiling	
Cut-out [mm]:	Ø76-Ø83mm	
Lifetime [h]:	L80B10: 100 000h	
Lumen/W:	80lm/W	
MacAdam (SDCM):	3	
Color:	Black	
Height [mm]:	45mm	
Width [mm]:	95mm	

Yes, recessed in insulation

Δ+