



PRODUCT SHEET

Driver 250-700mA cc (15-24/50V) LCA 17W one4All SR PRE DALI
Art. no: 28000670



Lighting Solutions

Driver 250-700mA cc (15-24/50V) LCA 17W one4All SR



SPECIFICATIONS

System Power [W]:	17W
Dimming:	CLO, Corridor, DALI2, Push, Ready2Mains
CC or CV:	CC
CC [mA]:	250 - 700mA
CC (forward voltage driver) [V]:	15 - 50V
Output Current Tolerance [%]:	3%
Current Ripple [%]:	5%
Current setting:	DALI-2, I-Select 2 Plug (Tridonic), Ready2Ma
Expected Lifetime:	100000h
Protection Class:	1 or 2
Dimming Minimum Level :	1%
Dimming output type:	Amplitude Modulation
Max load pr circuit - B10:	22
Max load pr circuit - B16:	36
Max load pr circuit - C10:	36
Max load pr circuit - C16:	60
Leakage current [mA]:	0,7mA
Inrush current I _{max} [A]:	18A
Inrush current time [μs]:	140μs
Manufacture:	Tridonic
Manufacture P/N:	28000670 - Driver 250-700mA cc (15-24/50V
Length:	200mm
Height:	31mm
Width:	70mm
Weight:	0,2kg