




FDV SPEC SHEET

Tania Mini 3-Circuit

Art. no: 3551-2-25-3-ddd



Lighting Solutions



Tania Mini 3-Circuit



Art. no: 3551-2-25-3-ddd

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	1050
Lumen LED (tc=25):	1450
Beam Angle:	25
CCT (Color Temperature):	2700
CRI / Ra:	90
Color Code:	927
MacAdam (SDCM):	3
Lens (Diffuser):	Clear

MOUNTING / CONNECTION

Connection:	Track 3-Circuit+dim
Mounting:	Track, Ceiling

ELECTRICAL DATA

Dimming:	DALI2
System Power [W]:	14,5
System Voltage [V]:	230V 50Hz
Dimming Output Type:	Amplitude Modulation
Protection Class:	1
Inrush current time [µs]:	0,72
Current Output [mA]:	350
Dimming Output Type:	Amplitude Modulation



FDV SPEC SHEET

Tania Mini 3-Circuit

Art. no: 3551-2-25-3-ddd



Lighting Solutions

PRODUCT

Ingress Protection:	IP20
Operating Temperature [°C]:	-20 - 40
Lifetime [h]:	L80B10: 55 000
Color:	White
Length [mm]:	167
Diameter [mm]:	60
Weight [kg]:	0,5
Housing Material :	Aluminium
Housing Material :	Aluminium