




## **Anka**





<b>(€</b> ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐	<b>∠</b> A <sup>**</sup>
SPECIFICATIONS	
Lightsource Type:	LED (built in)
System Power [W]:	59W
CCT (Color Temperature):	4000K
CRI / Ra:	70
Lumen Output:	8677lm
Lumen LED (tc=25):	9000lm
Beam Angle:	R4 Assymetric
Lens (Diffuser):	Clear
Dimming:	None
System Voltage [V]:	230V 50Hz
Connection:	Terminal
Mounting:	Wall, Mast
Lifetime [h]:	L90B10: 100 000h
Lumen/W:	148lm/W
MacAdam (SDCM):	3
Color:	Grey
Length [mm]:	525mm
Height [mm]:	102mm
Width [mm]:	250mm
Weight [kg]:	5,5kg

Anka is a luminaire for post mounting. We have developed this luminaire with an asymmetrical reflector giving a wide spread light, see light distribution diagram below. Anka has a post fixation opening with a diameter of 60mm. The luminaire has an IP66 classification and this guarantees that it will withstand very demanding conditions.