



FDV SPEC SHEET

Eta

Art. no: 687-02-3



Lighting Solutions



Eta



Art. no: 687-02-3

LIGHT TECHNICAL

| | |
|--------------------------|----------------|
| Lightsource Type: | LED (built in) |
| Lumen Output: | 1117 |
| Lumen LED (tc=25): | 1800 |
| CCT (Color Temperature): | 3000 |
| CRI / Ra: | 80 |
| Color Code: | 830 |
| Lens (Diffuser): | Opal |
| UGR (<=): | 21 |

MOUNTING / CONNECTION

| | |
|-------------|------------------------|
| Connection: | Terminal |
| Mounting: | Surface, Wall, Ceiling |

ELECTRICAL DATA

| | |
|--------------------------------------|-----------|
| Dimming: | None |
| System Power [W]: | 13 |
| System Voltage [V]: | 230V 50Hz |
| Protection Class: | 1 |
| Max load pr circuit - B10: | 31 |
| Max load pr circuit - B16: | 50 |
| Max load pr circuit - C10: | 52 |
| Max load pr circuit - C16: | 85 |
| Inrush current I _{max} [A]: | 5 |
| Inrush current time [μs]: | 50 |
| Current Output [mA]: | 500 |



FDV SPEC SHEET

Eta

Art. no: 687-02-3



Lighting Solutions

PRODUCT

| | |
|---------------------|----------------|
| Ingress Protection: | IP65 |
| Impact Protection: | IK08 |
| Corrosion Class: | C3 |
| Lifetime [h]: | L80B50: 50 000 |
| Color: | White |
| Height [mm]: | 130 |
| Width [mm]: | 360 |
| Weight [kg]: | 2,5 |