




FDV SPEC SHEET

Pavo P

Art. no: 8017646



Lighting Solutions



L, mm	W, mm	A, mm	B, mm	C, mm
280	95	135	87	77.5
360	105	196	104	123
410	115	239	157	149.5
500	140	317	191.5	124.5

Pavo P



Art. no: 8017646

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	2090
Lumen LED (tc=25):	2090
Beam Angle:	118
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
MacAdam (SDCM):	5
Lens (Diffuser):	Opal
UGR (<=):	22

MOUNTING / CONNECTION

Connection:	Terminal
Mounting:	Surface, Wall, Ceiling

ELECTRICAL DATA

Dimming:	None
System Power [W]:	22
System Voltage [V]:	230V 50Hz
Protection Class:	1
Socket / Cap-Base:	N/A
Emergency light [h]:	3 hours
Emergency light testing:	Selftest



FDV SPEC SHEET

Pavo P

Art. no: 8017646



Lighting Solutions

PRODUCT

Ingress Protection:	IP44
Impact Protection:	IK02
Operating Temperature [°C]:	-15 - 35
Lifetime [h]:	L70B50: 40 000
Color:	White
RAL:	RAL9003
Length [mm]:	410
Height [mm]:	115
Width [mm]:	410
Weight [kg]:	0,9