





FDV SPEC SHEET

Ledline


Art. no: 805003-3-ddd



Lighting Solutions



Ledline



Art. no: 805003-3-ddd

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	4090
Lumen LED (tc=25):	4900
Beam Angle:	110
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
Lens (Diffuser):	Opal

MOUNTING / CONNECTION

Connection:	LEDLine 5-pin
Mounting:	Recessed, Surface, Ceiling, Pendan

ELECTRICAL DATA

Dimming:	DALI
System Power [W]:	50
System Voltage [V]:	230V 50Hz
Protection Class:	2
Max load pr circuit - B10:	11
Max load pr circuit - B16:	18
Max load pr circuit - C10:	13
Max load pr circuit - C16:	21
Leakage current [mA]:	0,25
Inrush current Imax [A]:	60
Inrush current time [µs]:	3,5
Socket / Cap-Base:	N/A
Current Output [mA]:	560
Voltage Forward Min [V]:	32
Voltage Forward Max [V]:	48



FDV SPEC SHEET

Ledline

Art. no: 805003-3-ddd



Lighting Solutions

PRODUCT

Ingress Protection:	IP40
Impact Protection:	IK08
Lifetime [h]:	L80B10: 100 000
Color:	White
Length [mm]:	1500
Height [mm]:	84
Width [mm]:	56
Weight [kg]:	4,1