




**FDV SPEC SHEET**  
 Universal IP44  
 Art. no: 8071-105-3-ddd



## Universal IP44



Art. no: 8071-105-3-ddd

### LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	3650
Lumen LED (tc=25):	4000
Beam Angle:	105°
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
MacAdam (SDCM):	3
Lens (Diffuser):	PMMA Opal

### MOUNTING / CONNECTION

Connection:	QuickConnect
Mounting:	Surface, Ceiling

### ELECTRICAL DATA

Dimming:	DALI2
System Power [W]:	31
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	15
Max load pr circuit - B16:	24
Leakage current [mA]:	0,5
Inrush current I <sub>max</sub> [A]:	20
Inrush current time [µs]:	200
Socket / Cap-Base:	N/A



## FDV SPEC SHEET

Universal IP44

Art. no: 8071-105-3-ddd



*Lighting Solutions*

### PRODUCT

Ingress Protection:	IP44
Operating Temperature [°C]:	-20 - 25
Lifetime [h]:	L80B10: 100 000
Color:	White
Length [mm]:	1200
Height [mm]:	50
Width [mm]:	160
Weight [kg]:	2,9