



PRODUCT SHEET

Driver DALI 700mA (7-26) max 18W 18i5 DALI & SM Tridonic

Art. no: 87500921-700-03



Lighting Solutions

Driver DALI 700mA (7-26) max 18W 18i5 DALI & SM Trid



SPECIFICATIONS

| | |
|--------------------------------------|---|
| System Power [W]: | 20W |
| Dimming: | CLO, Corridor, DALI, DALI2, Push |
| Standby power P _{sb} (W) <: | 0,4 |
| Flicker metric (Pst LM) <: | 1 |
| Stroboscopic effect metric (SVM) <: | 0,4 |
| CC or CV: | CC |
| CC [mA]: | 100 - 1050mA |
| Max output voltage [V]: | 60 |
| Output Current Tolerance [%]: | 5% |
| Current Ripple [%]: | 5% |
| Current setting: | DALI-2, NFC |
| Expected Lifetime: | 100000h |
| System Voltage [V]: | 230V 50Hz V |
| Protection Class: | 2 |
| Dimming Minimum Level : | 1% |
| Dimming output type: | Amplitude Modulation |
| Max load pr circuit - B10: | 70 |
| Max load pr circuit - B16: | 112 |
| Max load pr circuit - C10: | 70 |
| Max load pr circuit - C16: | 112 |
| Leakage current [mA]: | 0,7mA |
| Inrush current I _{max} [A]: | 10A |
| Inrush current time [μs]: | 80μs |
| Manufacture: | Tridonic |
| Manufacture P/N: | 87500921 - Driver LC 20W 100-1050mA 44V |
| Primary Connection: | 18i5 DALI male |
| Secondary Connection: | SM Connector |



PRODUCT SHEET

Driver DALI 700mA (7-26) max 18W 18i5 DALI & SM Tridonic
Art. no: 87500921-700-03



Lighting Solutions

| | |
|-----------------------------|----------|
| Length: | 120mm |
| Height: | 29mm |
| Width: | 51mm |
| Weight: | 0,1kg |
| Operating Temperature [°C]: | -20 - 45 |